



Hicks Oils  
845 N. Hickory  
DuQuoin, IL 62832

Sales: (314) 525-2568  
Operations: (618) 542-5431

# **FORMULA** **500**

## **Super V Synthetic Blend Multivehicle Automatic Transmission Fluid**

**Formula 500®** Synthetic Blend Super V is an automatic transmission fluid specifically designed to work in a wide variety of automatic transmissions. Formula 500® Synthetic blend Super V uses high quality synthetic and petroleum base stocks along with state of the art additive technology to create a high quality product that is more economical than a full synthetic fluid. The Super V formulation has been extensively field tested to demonstrate the fluids compatibility in a variety of types and brands of automatic transmissions. Formula 500® Super V automatic transmission fluid demonstrates excellent protection from wear, sludge buildup, and corrosion in the transmission. Refer to table for compatibility with specific types of transmissions.

### **Features:**

- Incorporates a blend of both synthetic and petroleum base stocks
- Protects metal parts from corrosion
- Provides excellent oxidative stability under severe conditions
- Reduces sludge and varnish build-up
- Protects transmission gears and allows them to operate smoothly
- Maintains lubricity
- Flows well for cold start-up
- Provides excellent shift feel with no shudder
- Prevents fluid breakdown at higher operating temperatures
- Thoroughly field tested
- Performance surpasses minimum specifications



Hicks Oils  
845 N. Hickory  
DuQuoin, IL 62832

Sales: (314) 525-2568  
Operations: (618) 542-5431

## Typical Properties:

Product: Super V Synthetic Blend Automatic Transmission Fluid	
Product Code	90163
Color	Amber brown
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	7.6
Kinematic Viscosity @ 40 °C cSt (ASTM D-445)	38.0
Viscosity Index (ASTM D-2270)	173
API Gravity (ASTM D-1298)	32.0

## Super V synthetic blend automatic transmission fluid is suitable for use in these applications:

- Allison C-4
- Audi G 052-025-A2
- Audi G-052-162-A1
- BMW 7045E
- BMW LA2634
- BMW LT 71141
- Chrysler ATF's
- Dexron®
- Dexron®-II
- Dexron®-II D
- Dexron®-III G
- Dexron®-III H
- Esso LT 71141
- Ford FNR5
- Ford Mercon®
- Ford Mercon® V
- Honda ATF-Z1
- Hyundai SP-II & SP-III
- Idemitsu K17
- JASO 1-A
- JWS 3309
- Kia SP-II
- KIA SP-III
- MAN 339: F, V1, V2, Z1, Z2
- Mazda ATF-MIII
- Mazda ATF-MV
- Mercedes Benz: 236.1, 236.2, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11
- Mitsubishi Diamond SP-II, SP-III
- Nissan Matic-D
- Nissan Matic-J, Matic K
- Shell 3403
- Shell LA 2634
- Subaru ATF, ATF-HP
- Texaco ETL: 7045E,8072B
- Texaco N402
- Toyota T-III, IV
- Voith 55.6335.XX (G607),(G1363
- Volvo Pass Car (4-6 sp)
- Volvo; 97340, 97341
- VW G 052-025-A2
- VW G 052-162-A1
- ZF TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C

Formula 500 ® synthetic blend Super V automatic transmission fluid is not recommended for: Allison TES-389, Ford Type F, Ford Mercon® SP & LV, and Mercedes Benz 236.5, 236.12, 236.14. Always follow manufacturers' recommendations.