



Hicks Oils  
845 N. Hickory  
DuQuoin, IL 62832

Sales: (314) 525-2568  
Operations: (618) 542-5431

# NATURE'S Choice®

## Nature's Choice® CF/SJ Monograde Diesel Motor Oils

**Nature's Choice®** CF-2, CF/SJ Diesel motor oils are for use in diesel engines under service conditions from mild to heavy duty with fuel of any sulfur level. The current formulations meet API Service Classifications up to CF, CF-2. Several viscosity grades are also suitable where Allison C-4 or Caterpillar TO-2 fluids are specified follow the performance specifications below.

The Nature's Choice® product line was developed in response to President Clinton's Executive Order 13101 which mandated the use of motor oils with re-refined content for government use. Since that time the Nature's Choice® product line has grown from motor oils to include many other types of lubrication. Blending virgin and re-refined base stocks with quality additive chemistry, Nature's Choice® brand products are able to meet the top performance grades required for today's lubrication requirements, while being more environmentally friendly.

These oils should not be used in Caterpillar TO-4 applications, two-cycle gasoline engines, aircraft engines, or EMD Diesel engines.

### Performance Specifications:

Product Code Specification	101111 10W	101112 20W	101113 30	101114 40	101115 50
API CD*	X	X	X	X	X
API CD-II*			X	X	X
API CE*	X	X	X	X	X
API CF	X	X	X	X	X
API CF-2			X	X	X
API SH	X	X	X	X	X
API SJ		X	X	X	X
Allison C-4	P		P		
CAT TO-2	X	X	X	X	

X = Meets requirements \* = Obsolete Service Category P = Meets performance requirements, follow viscosity

### Typical Properties:

Product Code	101111	101112	101113	101114	101115
SAE Viscosity Grade	10W	20W	30	40	50
API Gravity	30.8	30.0	28.0	27.0	27.0
Viscosity, 40 C, cSt	44	63	95	135	200
Viscosity, 100 C, cSt	7.0	8.5	11.0	14.0	18.0
Viscosity Index	110	105	105	100	100
TBN	9.0	9.0	9.0	9.0	9.0
Sulfated Ash, wt%	1.20	1.20	1.20	1.20	1.20