



Hicks Oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431

NATURE'S Choice®

Nature's Choice® CI-4/SL Multigrade Diesel Motor Oils

Nature's Choice® CI-4/SL diesel motor oils are for use in diesel engines under service conditions from mild to heavy duty with fuel of any sulfur level. These oils are recommended for use in nearly all two- and four-cycle diesel applications. The current formulation is licensed by the API as a CI-4/SL motor oil and also is recommended for use in older API service classifications, Mack specifications EO-M Plus and Cummins CES 20078. Nature's Choice® CI-4/SL diesel motor oils also meet the performance requirements of Allison C-4 and Caterpillar TO-2, in addition they meet the Caterpillar ECF-1 specification.

The Nature's Choice® product line was developed in response to President Clinton's Executive Order 13101 which mandated the use of motor oils with re-refined content for government use. Since that time the Nature's Choice® product line has grown from motor oils to include many other types of lubrication. Blending virgin and re-refined base stocks with quality additive chemistry, Nature's Choice® brand products are able to meet the top performance grades required for today's lubrication requirements, while being more environmentally friendly.

These oils should not be used in Caterpillar TO-4 applications, two-cycle gasoline engines, aircraft engines, or EMD Diesel engines.

Typical Properties:

Product:	Nature's Choice CI-4/SL Motor Oil		
API Classification	CI-4/SL	CI-4/SL 15W-40	CI-4/SL 15W-40
SAE Viscosity Grade	15W-40	15W-40	15W-40
Product Code	141119	142119	143119
TBN (ASTM D-2896)	9.4	10	12
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	14.3	13.8	14.0
Kinematic Viscosity @ 40 °C cSt (ASTM D-445)	102.9	103.9	105.0
Viscosity Index (ASTM D-2270)	141	135	140
API Gravity (ASTM D-1298)	29.0	29.1	29.0
Pour Point °C (°F) (ASTM D-97)	-18(0)	-18(0)	-18(0)
Flash Point °C (°F) (ASTM D-92)	222(431)	222(431)	222(431)