



Hicks Oils  
845 N. Hickory  
DuQuoin, IL 62832

Sales: (314) 525-2568  
Operations: (618) 542-5431

# NATURE'S Choice®

## Nature's Choice® 10W-30, 10W-40, 20W-50 SM Motor Oils

**Nature's Choice®** API Service SM motor oils are designed to meet the high performance requirements initiated in 2005 automotive lines. Nature's Choice® API SM 10W-30, 10W-40, and 20W-50 motor oils use high quality re-refined and conventional petroleum base stocks along with state of the art additive technology to create a high quality motor oil for use in gasoline powered engines. These API licensed motor oils provide protection against wear and deposits in the engine, while extending the life of emission control components. This premium blend of motor oil allows up to 5,000 miles between oil changes.

These oils carry the American Petroleum Institute SM approvals, and the 10W-30 grade also carries the ILSAC GF-4 approval. The API donut and ILSAC starburst identify oils which have undergone the necessary testing to meet current automotive specification. In addition the API tests samples from the market place to verify compliance with current specifications. These oils also meet all older API gasoline specifications (SL, SJ, SH, etc...).

The Nature's Choice® product line was developed in response to President Clinton's Executive Order 13101 which mandated the use of motor oils with re-refined content for government use. Since that time the Nature's Choice® product line has grown from motor oils to include many other types of lubrication. Blending virgin and re-refined base stocks with quality additive chemistry, Nature's Choice® brand products are able to meet the top performance grades required for today's lubrication requirements, while being more environmentally friendly

Always follow manufacturer's recommendations for Service classification and viscosity grade.

### Typical Properties:

Product	Nature's Choice Motor Oils		
	10W-30	10W-40	20W-50
SAE Viscosity Grade	10W-30	10W-40	20W-50
API Classification, (ILSAC Classification)	SM (GF-4)	SM	SM
Product Code	141127	141128	141120
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	10.4	15.5	18.2
Kinematic Viscosity @ 40 °C cSt (ASTM D-445)	68	106	161
Viscosity Index (ASTM D-2270)	139	155	126
Total Base Number (ASTM D-2896)	8.3	8.2	8.1
Flash Point °C (°F) (ASTM D-92)	244 (471)	204(399)	204(399)
Pour Point °C (°F) (ASTM D-97)	-39(-38)	-30(-22)	-21(-6)
API Gravity (ASTM D-1298)	30.6	30.6	29.4
Zn (ppm)	853	853	853
Ca (ppm)	2146	2146	2146
P (ppm)	774	774	774