



Hicks Oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Synthetic JASO MA2 API SM Motorcycle Oils

Venom® full synthetic JASO MA2, API SM motorcycle oils are a three tiered line of premium full synthetic motorcycle oils, specifically designed to meet the most current performance requirements of the JASO MA2 and API SM service standards. All of Venom's synthetic JASO MA2, API SM motorcycle oils use a state of the art additive package that has been designed and tested to provide excellent wear protection, prevention from rust and oxidation, provide optimal clutch performance, and maintain proper frictional characteristics as required by the current JASO standards. All three tiers of the product use full synthetic base oils with high shear stability viscosity modifiers and are available in SAE viscosities of 10W-40 and 20W-50.

Standard Full Synthetic JASO MA2, API SM Motorcycle Oil:

Venom® Full Synthetic JASO MA2 API SM Standard Motorcycle oil uses current state of the art additive technology in a full synthetic base stock to meet the requirements of the current JASO MA2 and API SM service standards.

Premium Full Synthetic JASO MA2, API SM Motorcycle Oil:

Venom® Full Synthetic JASO MA2 API SM Premium Motorcycle oil uses the same state of the art additive technology as the standard formulation in a full synthetic base stock but also contains an additional performance additive designed to increase the oils detergency characteristics that helps to promote cleanliness within the operating system.

Ultimate Premium Full Synthetic JASO MA2, API SM Motorcycle Oil:

Venom® Full Synthetic JASO MA2 API SM Ultimate Premium Motorcycle oil is in the upper tier of motor cycle oils offered in the market place today. This Ultimate Premium formulation uses the same lab and field proven state of the art additive that provides for JASO MA2 API SM quality oil with the addition of other performance additives to provide extended protection and performance properties beyond the current service classifications. The additional additives provide superior performance and protection by using:

- Enhanced detergency to promote cleanliness in the operating system
- An ashless dispersant that inhibits sludge build up especially under hard riding conditions and extremes in temperatures
- Additional friction modifiers to ensure superior clutch performance and gear protection

Refer to individual typical properties sheets for more specific information and product codes.



Hicks Oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Standard Synthetic JASO MA2 API SM Motorcycle Oils

Venom® standard synthetic JASO MA2, API SM motorcycle oils are full synthetic motorcycle oils, specifically designed to meet the most current performance requirements of the JASO MA2 and API SM service standards. Venom® standard synthetic JASO MA2, API SM motorcycle oils use a state of the art additive package that has been designed and tested to provide excellent wear protection, prevention from rust and oxidation, provide optimal clutch performance, and maintain proper frictional characteristics as required by the current JASO MA2 standard. These oils use full synthetic base oils with high shear stability viscosity modifiers and are available in SAE viscosities of 10W-40 and 20W-50.

Typical Properties:

Product: Venom Standard Synthetic JASO MA2 API SM Motorcycle Oils		
Product Code	90150	90153
JASO, API Classification	MA2, SM	MA2, SM
SAE viscosity grade	10W-40	20W-50
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	15.5	19.7
Kinematic Viscosity @ 40 °C cSt (ASTM D-445)	112.0	160.0
Viscosity Index (ASTM D-2270)	146	142



Hicks Oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Premium Synthetic JASO MA2 API SM Motorcycle Oils

Venom® premium synthetic JASO MA2, API SM motorcycle oils are full synthetic motorcycle oils, specifically designed to meet and exceed the most current performance requirements of the JASO MA2 and API SM service standards. Venom® premium synthetic JASO MA2, API SM motorcycle oils use a state of the art additive package that has been designed and tested to provide excellent wear protection, prevention from rust and oxidation, provide optimal clutch performance, and maintain proper frictional characteristics as required by the current JASO MA2 standard. Additional ashless performance additives are added to increase the oils detergency. This increase in ashless detergency provides cleanliness beyond the JASO standard throughout the system by absorbing foreign contaminants. These oils use full synthetic base oils with high shear stability viscosity modifiers and are available in SAE viscosities of 10W-40 and 20W-50.

Typical Properties:

Product: Venom Premium Synthetic JASO MA2 API SM Motorcycle Oils		
Product Code	90156	90159
JASO, API Classification	MA2, SM	MA2, SM
SAE viscosity grade	10W-40	20W-50
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	15.5	19.7
Kinematic Viscosity @ 40 °C cSt (ASTM D-445)	112.0	160.0
Viscosity Index (ASTM D-2270)	146	142



Hicks Oils
845 N. Hickory
DuQuoin, IL 62832

Sales: (314) 525-2568
Operations: (618) 542-5431



Ultimate Premium Synthetic JASO MA2 API SM Motorcycle Oils

Venom® ultimate premium synthetic JASO MA2, API SM motorcycle oils are among the higher tiered synthetic motorcycle oils in the market place today. These full synthetic motorcycle oils are specifically designed to meet and exceed the most current performance requirements of the JASO MA2 and API SM service standards. Venom® ultimate premium synthetic JASO MA2, API SM motorcycle oils use a state of the art additive package that has been designed and tested to provide excellent wear protection, prevention from rust and oxidation, provide optimal clutch performance, and maintain proper frictional characteristics as required by the current JASO MA2 standard. Venom® ultimate premium synthetic JASO MA2 API SM motorcycle oil has been developed with additional performance additives to create an oil that exceeds the current certification standards. The additional additives provide superior performance and protection by using:

- Enhanced detergency to promote cleanliness in the operating system
- An ashless dispersant that inhibits sludge build up especially under hard riding conditions and extremes in temperatures
- Additional friction modifiers to ensure superior clutch performance and gear protection

These oils use full synthetic base oils with high shear stability viscosity modifiers and are available in SAE viscosities of 10W-40 and 20W-50.

Typical Properties:

Product: Venom Ultimate Premium Synthetic JASO MA2 API SM Motorcycle Oils		
Product Code	90089	90090
JASO, API Classification	MA2, SM	MA2, SM
SAE viscosity grade	10W-40	20W-50
Kinematic Viscosity @ 100 °C cSt (ASTM D-445)	15.5	19.7
Kinematic Viscosity @ 40 °C cSt (ASTM D-445)	110.6	154.6
Viscosity Index (ASTM D-2270)	148	146